



Declaration of Performance (DoP)

No. F 163-CPR-20130821	
Product Type:	Roomheaters fired by solid fuel
Type, batch or serial number:	Jøtul F 160 Series (Jøtul F 163, Jøtul F 163 C, Jøtul F 165, Jøtul F 167, Jøtul F 167 C)
Intended use of the product:	Roomheater burning solid fuel without water supply
Name and Address of the manufacturer:	Jøtul AS Postboks 1411, 1602 Fredrikstad, Norway Tel.: +47 69 35 90 00 E-mail: post@jotul.no
AVCP: <i>System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V</i>	System 3
Notified body: NB-No: Test report no:	RWE Power AG, Feuerstättenprüfstelle 1427 FSPS-Wa 1964-EN, FSPS-Wa 2009-EN, FSPS-Wa 2154-EN
Declared performance:	
Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety Reaction to fire Distance to combustible materials	A1 Minimum distances, in mm F 163, F 165, F 167 (F 163 C, F 167 C) Rear = 200 (100) Sides = 600 (200) Corner = 500 (200) Front = 1000 (1000) <i>See also the installation instructions</i>
Risk of burning fuel falling out	No
Emission of combustion products	CO [0,099%] NOx [120 mg/m ³] OGC [107 mgC/m ³] PM [20 mg/m ³]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	-
Flue gas temperature at nominal heat output	T [200°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output Normal heat output Room heating output Water heating output	5 kW - kW -*kW
Energy efficiency	η [82%]

Declaration:

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Tom J. Berglind

R&D Manager

(Name and function)

Fredrikstad, August 21st, 2013

(Place and date of issue)

Tom J. Berglind

(Signature)